

# SQL\*Plus®

Quick Reference

Release 11.1

B31190-01

July 2007

---

## About this Quick Reference

This Quick Reference shows SQL\*Plus command syntax. For detailed information on each command, refer to the *SQL\*Plus User's Guide and Reference*.

This Quick Reference has the following topics:

- [Documentation Accessibility](#)
- [Alphabetic List of SQL\\*Plus Commands](#)
- [Starting and Leaving SQL\\*Plus](#)
- [Starting Up and Shutting Down a Database](#)
- [Entering and Executing Commands](#)
- [Manipulating SQL, SQL\\*Plus and PL/SQL Commands](#)
- [Formatting Query Results](#)
- [Accessing Databases](#)
- [Miscellaneous](#)

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

## Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

## TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

## Alphabetic List of SQL\*Plus Commands

@{url | file\_name[.ext]} [arg ...]

@@ { url | file\_name[.ext] } [arg ...]

/ (slash)

ACC[EPT] *variable* [NUM[BER] | CHAR | DATE | BINARY\_FLOAT | BINARY\_DOUBLE] [FOR[MAT] *format*] [DEF[AULT] *default*] [PROMPT *text* | NOPR[OMPT]] [HIDE]

A[PPEND] *text*

ARCHIVE LOG {LIST | STOP} | {START | NEXT | ALL | *integer*} [TO *destination*]

ATTRIBUTE [*type\_name.attribute\_name* [option...]]

BRE[AK] [ON *report\_element* [action [action]]] ...

BTI[TLE] [*printspec* [*text* | *variable*] ...] | [ON | OFF]

C[HANGE] *sepchar old* [*sepchar* [*new* [*sepchar*]]]

CL[EAR] *option* ...

COL[UMN] [{*column* | *expr*} [option ...]]

COMP[UTE] [*function* [LAB[EL] *text*] ... OF {*expr* | *column* | *alias*} ...ON {*expr* | *column* | *alias* | REPORT | ROW} ...]

CONN[ECT] [{*logon* | /} [AS {SYSOPER | SYSDBA | SYSASM}]]

COPY {FROM *database* | TO *database* | FROM *database* TO *database*} {APPEND | CREATE | INSERT | REPLACE} *destination\_table*[(*column*, *column*, *column*, ...)] USING *query*

DEF[INE] [*variable*] | [*variable* = *text*]

DEL [*n* | *n m* | *n \** | *n LAST* | \* | \* *n* | \* LAST | LAST]

DESC[RIBE] [{*schema*.]*object*[@*connect\_identifier*]

DISC[ONNECT]

ED[IT] [*file\_name*[.ext]]

EXEC[UTE] *statement*

{EXIT | QUIT} [SUCCESS | FAILURE | WARNING | *n* | *variable* | :*BindVariable*] [COMMIT | ROLLBACK]

GET [FILE] *file\_name*[.ext] [LIST | NOLIST]

HELP | ? [*topic*]

HO[ST] [*command*]

I[INPUT] [*text*]  
 L[IST] [*n* | *n m* | *n \** | *n LAST* | *\* | \* n* | *\* LAST* | *LAST*]  
 PASSW[ORD] [*username*]  
 PAU[SE] [*text*]  
 PRI[NT] [*variable ...*]  
 PRO[MPT] [*text*]  
 {QUIT | EXIT} [SUCCESS | FAILURE | WARNING | *n* | *variable*  
 | *:BindVariable*] [COMMIT | ROLLBACK]  
 RECOVER {*general* | *managed* | BEGIN BACKUP | END BACKUP}  
 REM[ARK]  
 REPF[OOTER] [PAGE] [*printspectext* | *variable* ...] | [ON | OFF]  
 REPH[EADER] [PAGE] [*printspectext* | *variable* ...] | [ON | OFF]  
 R[UN]  
 SAV[E] [*FILE*] *file\_name* [*.ext*] [CRE[ATE] | REP[LACE] | APP[END]]  
 SET *system\_variable value*  
 SHO[W] [*option*]  
 SHUTDOWN [ABORT | IMMEDIATE | NORMAL | TRANSACTIONAL [LOCAL]]  
 SPO[OL] [*filename* [*.ext*] [CRE[ATE] | REP[LACE] | APP[END]] | OFF | OUT]  
 STA[RT] { *url* | *file\_name* [*.ext*] } [*arg ...*]  
 STARTUP *options* | *upgrade\_options*  
 STORE {SET} *file\_name* [*.ext*] [CRE[ATE] | REP[LACE] | APP[END]]  
 TIMI[NG] [START *text* | SHOW | STOP]  
 TTI[TLE] [*printspectext* | *variable* ...] | [ON | OFF]  
 UNDEF[INE] *variable ...*  
 VAR[IABLE] [*variable* [*type*]]  
 WHENEVER OSERROR {EXIT [SUCCESS | FAILURE | *n* | *variable* | *:BindVariable*] [COMMIT |  
 ROLLBACK] | CONTINUE[COMMIT | ROLLBACK | NONE]}  
 WHENEVER SQLERROR {EXIT [SUCCESS | FAILURE | WARNING | *n* | *variable*  
 | *:BindVariable*] [COMMIT | ROLLBACK] | CONTINUE [COMMIT | ROLLBACK | NONE]}  
 XQUERY *xquery\_statement*

## Starting and Leaving SQL\*Plus

**Use the following commands to log in to and out of SQL\*Plus.**

SQLPLUS [[*option*] [*logon*] [*start*]]

where *option* has the following syntax:

-H[ELP]  
 | -V[ERSION]  
 | [ [-C[OMPATIBILITY] *x.y[.z]*] [-F[AILOVER]] [-L[OGON]]

```
[-M[ARKUP] "mark_options"] [-R[ESTRICT] {1 | 2 | 3}] [-S[ILENT]] ]
```

where *mark\_options* has the following syntax:

```
HTML [ON | OFF] [HEAD text] [BODY text] [TABLE text]  
[ENTMAP {ON | OFF}] [SPOOL {ON | OFF}] [PRE[FORMAT] {ON | OFF}]
```

where *logon* has the following syntax:

```
{username[/password] [@connect_identifier] | /}  
[AS {SYSOPER | SYSDBA | SYSASM}] | /NOLOG
```

and where *start* has the following syntax:

```
@{url | file_name[.ext]} [arg ...]
```

```
{EXIT | QUIT} [SUCCESS | FAILURE | WARNING | n | variable  
| :BindVariable] [COMMIT | ROLLBACK]
```

Commits or rolls back all pending changes, logs out of Oracle, terminates SQL\*Plus and returns control to the operating system.

## Starting Up and Shutting Down a Database

Starting up and shutting down a database requires DBA privileges.

```
STARTUP options | upgrade_options
```

where *options* has the following syntax:

```
[FORCE] [RESTRICT] [PFILE=filename] [QUIET] [ MOUNT [dbname] |  
[ OPEN [open_options] [dbname] ] | NOMOUNT ]
```

where *open\_options* has the following syntax:

```
READ {ONLY | WRITE [RECOVER]} | RECOVER
```

and where *upgrade\_options* has the following syntax:

```
[PFILE=filename] {UPGRADE | DOWNGRADE} [QUIET]
```

Starts an Oracle instance with several options, including mounting and opening a database.

```
SHUTDOWN [ABORT | IMMEDIATE | NORMAL | TRANSACTIONAL [LOCAL]]
```

Shuts down a currently running Oracle instance, optionally closing and dismounting a database.

## Entering and Executing Commands

**Use the following commands to execute and collect timing statistics on SQL commands and PL/SQL blocks.**

```
/(slash)
```

Executes the most recently executed SQL command or PL/SQL block which is stored in the SQL buffer. Does not list the command. Use slash (/) at the command prompt or line number prompt in SQL\*Plus command line. The buffer has no command history and does not record SQL\*Plus commands.

EXEC[UTE] *statement*

Executes a single PL/SQL statement or runs a stored procedure.

R[UN]

Lists and executes the most recently executed SQL command or PL/SQL block which is stored in the SQL buffer. The buffer has no command history and does not record SQL\*Plus commands.

TIM[ING] [START *text* | SHOW | STOP]

Records timing data for an elapsed period of time, lists the current timer's name and timing data, or lists the number of active timers.

**Use the following command to access the help system.**

HELP | ? [*topic*]

Accesses the command-line help system. Enter HELP INDEX or ? INDEX for a list of topics. You can view SQL\*Plus resources at

[http://www.oracle.com/technology/tech/sql\\_plus/](http://www.oracle.com/technology/tech/sql_plus/) and the Oracle Database Library at

<http://www.oracle.com/technology/documentation>.

**Use the following command to execute operating system commands.**

HO[ST] [*command*]

Executes an operating system command without leaving SQL\*Plus. Enter HOST without command to display an operating system prompt. You can then enter multiple operating system commands.

With some operating systems, you can use another character instead of HOST such as "!" (UNIX) and "\$" (Windows). See the Oracle installation and user's manuals provided for your operating system for details.

## Manipulating SQL, SQL\*Plus and PL/SQL Commands

**Use the following commands to edit SQL commands and PL/SQL blocks.**

A[PPEND] *text*

Adds specified text to the end of the current line in the SQL buffer. To separate *text* from the preceding characters with a space, enter two spaces. To append *text* that ends with a semicolon, end the command with two semicolons (a single semicolon is interpreted as a command terminator).

C[HANGE] *sepchar old [sepchar [new [sepchar]]]*

Changes first occurrence of *old* on the current line of the SQL buffer. You can use any non-alphanumeric character such as "/" or "!" as a *sepchar*. You can omit the space between CHANGE and the first *sepchar*. The buffer has no command history list and does not record SQL\*Plus commands.

DEL [*n* | *n m* | *n \** | *n LAST* | *\** | *\* n* | *\* LAST* | *LAST*]

Deletes one or more lines of the SQL buffer ("\*" indicates the current line). You can omit the space between DEL and *n* or *\**, but not between DEL and LAST.

Enter DEL with no clauses to delete the current line of the buffer. The buffer has no command history list and does not record SQL\*Plus commands.

!**[NPUT]** [*text*]

Adds one or more new lines of text after the current line in the SQL buffer. The buffer has no command history list and does not record SQL\*Plus commands.

**L[IST]** [*n* | *n m* | *n \** | *n LAST* | *\** | *\* n* | *\* LAST* | *LAST*]

Lists one or more lines of the most recently executed SQL command or PL/SQL block which is stored in the SQL buffer. Asterisk (\*) indicates the current line. You can omit the space between LIST and *n* or *\**, but not between LIST and LAST. Enter LIST with no clauses to list all lines. The buffer has no command history list and does not record SQL\*Plus commands.

**Use the following commands to run scripts.**

**@** { *url* | *file\_name*[.ext] } [*arg* ...]

Runs the SQL\*Plus statements in the specified script. The script can be called from the local file system or a web server. You can pass values to script variables in the usual way.

**@@** { *url* | *file\_name*[.ext] } [*arg* ...]

Runs the SQL\*Plus statements in the specified script. This command is almost identical to the @ command. It is useful for running nested scripts because it has the additional functionality of looking for the specified script in the same path or *url* as the calling script.

**STA[RT]** { *url* | *file\_name*[.ext] } [*arg* ...]

Runs the SQL\*Plus statements in the specified script. The script can be called from the local file system or a web server. You can pass values to script variables in the usual way.

**Use the following commands to create and modify scripts.**

**ED[IT]** [*file\_name*[.ext]]

Invokes an operating system text editor on the contents of the specified file or on the contents of the SQL buffer. To edit the buffer contents, omit the file name. The buffer has no command history list and does not record SQL\*Plus commands.

**GET** *file\_name*[.ext] [*LIST* | *NOLIST*]

Loads a SQL statement or PL/SQL block from a file into the SQL buffer. The buffer has no command history list and does not record SQL\*Plus commands.

**REM[ARK]**

Begins a comment in a script. The REMARK command must appear at the beginning of a line, and the comment ends at the end of the line (a line cannot contain both a comment and a command). SQL\*Plus does not interpret the comment as a command.

SAV[E] *file\_name* [.ext] [CRE[ATE] | REP[LACE] | APP[END]]

Saves the contents of the SQL buffer in a file. The buffer has no command history list and does not record SQL\*Plus commands.

STORE {SET} *file\_name* [.ext] [CRE[ATE] | REP[LACE] | APP[END]]

Saves attributes of the current SQL\*Plus environment in a file.

WHENEVER OSERROR {EXIT [SUCCESS | FAILURE | *n* | *variable*  
| :*BindVariable*] [COMMIT | ROLLBACK] | CONTINUE [COMMIT | ROLLBACK | NONE]}

Performs the specified action (exits SQL\*Plus by default) if an operating system error occurs (such as a file writing error).

WHENEVER SQLERROR {EXIT [SUCCESS | FAILURE | WARNING | *n* | *variable*  
| :*BindVariable*] [COMMIT | ROLLBACK] | CONTINUE [COMMIT | ROLLBACK | NONE]}

Performs the specified action (exits SQL\*Plus by default) if a SQL command or PL/SQL block generates an error.

**Use the following commands to write interactive commands.**

ACC[EPT] *variable* [NUM[BER] | CHAR | DATE | BINARY\_FLOAT | BINARY\_DOUBLE] [FOR[MAT]  
*format*] [DEF[AULT] *default*] [PROMPT *text* | NOPR[OMPT]] [HIDE]

Reads a line of input and stores it in a given substitution variable.

DEF[INE] [*variable*] | [*variable* = *text*]

Specifies a substitution variable and assigns a CHAR value to it, or lists the value and variable type of a single variable or all variables.

PAU[SE] [*text*]

Displays the specified text then waits for the user to press RETURN.

PRO[MPT] [*text*]

Sends the specified message or a blank line to the user's screen.

UNDEF[INE] *variable* ...

Deletes one or more substitution variables that you defined either explicitly (with the DEFINE command) or implicitly (with a START command argument).

**Use the following commands to create and display bind variables.**

PRI[NT] [*variable* ...]

Displays the current values of bind variables, or lists all bind variables.

VAR[IABLE] [*variable* [*type*]]

where *type* represents one of the following:

NUMBER  
CHAR  
CHAR (*n* [CHAR | BYTE])  
NCHAR  
NCHAR (*n*)  
VARCHAR2 (*n* [CHAR | BYTE])  
NVARCHAR2 (*n*)  
BLOB  
BFILE  
CLOB  
NCLOB  
REFCURSOR  
BINARY\_FLOAT  
BINARY\_DOUBLE

Declares a bind variable that can be referenced in PL/SQL, or lists the current display characteristics for a single variable or all variables.

**Use the following symbols to create substitution variables and parameters for use in scripts.**

*&n*

Specifies a parameter in a script you run using the START command. START substitutes values you list after the script name as follows: the first for &1, the second for &2, and so on.

*&user\_variable, &&user\_variable*

Indicates a substitution variable in a SQL or SQL\*Plus command. SQL\*Plus substitutes the value of the specified substitution variable for each substitution variable it encounters. If the substitution variable is undefined, SQL\*Plus prompts you for a value *each* time an "&" variable is found, and the *first* time an "&&" variable is found.

*.* (period)

Terminates a substitution variable followed by a character that would otherwise be part of the variable name.

## Formatting Query Results

**Use the following commands to format, store and print your query results.**

ATTRIBUTE [*type\_name.attribute\_name* [*option...*]]

Specifies display characteristics for a given attribute of an Object Type column, such as the format of NUMBER data. Columns and attributes should not have the same names as they share a common namespace. Lists the current display characteristics for a single attribute or for all attributes.

Where *option* represents one of the following clauses:

ALI[AS] *alias*

CLE[AR]

FOR[MAT] *format*

LIKE {*type\_name.attribute\_name* | *alias*}



ON | OFF

BRE[AK] [ON *report\_element* [*action* [*action*]]] ...

Specifies where changes occur in a report and the formatting action to perform, such as:

- suppressing the display of duplicate values for a given column
- skipping a line each time a given column value changes
- printing computed figures each time a given column value changes or at the end of the report

Enter BREAK with no clauses to list the current BREAK definition.

Where *report\_element* has the following syntax:

{*column* | *expr* | ROW | REPORT}

and where *action* has the following syntax:

[SKI[P] *n* | [SKI[P]] PAGE] [NODUP[LICATES] | DUP[LICATES]]

BTI[TLE] [*printspec* [*text* | *variable*] ...] | [ON | OFF]

Places and formats a title at the bottom of each report page, or lists the current BTITLE definition. Use one of the following clauses in place of *printspec*:

BOLD  
CE[NTER]  
COL *n*  
FORMAT *text*  
LE[FT]  
R[IGHT]  
S[KIP] [*n*]  
TAB *n*

CL[EAR] *option* ...

Resets or erases the current value or setting for the specified option.

Where *option* represents one of the following clauses:

BRE[AKS]  
BUFF[ER]  
COL[UMNS]  
COMP[UTES]  
SCR[EEN]  
SQL  
TIMI[NG]

COL[UMN] [{*column* | *expr*} [*option* ...]]

Specifies display attributes for a given column, such as:

- text for the column heading
- alignment for the column heading
- format for NUMBER data

- wrapping of column data

Also lists the current display attributes for a single column or all columns.

Where *option* represents one of the following clauses:

ALI[AS] *alias*  
 CLE[AR]  
 ENTMAP {ON | OFF}  
 FOLD\_A[FTER]  
 FOLD\_B[EFORE]  
 FOR[MAT] *format*  
 HEA[DING] *text*  
 JUS[TIFY] {L[EFT] | C[ENTER] | R[IGHT]}  
 LIKE {*expr* | *alias*}  
 NEWL[INE]  
 NEW\_V[ALUE] *variable*  
 NOPRI[NT] | PRI[NT]  
 NUL[L] *text*  
 OLD\_V[ALUE] *variable*  
ON | OFF  
WRA[PPED] | WOR[D\_WRAPPED] | TRU[NCATED]

Enter COLUMN [{*column* | *expr*} FORMAT *format*] where the *format* element specifies the display format for the column.

To change the display format of a NUMBER column, use FORMAT followed by one of the elements in the following table:

Element	Examples	Description
, (comma)	9,999	Displays a comma in the specified position.
. (period)	99.99	Displays a period (decimal point) to separate the integral and fractional parts of a number.
\$	\$9999	Displays a leading dollar sign.
0	0999 9990	Displays leading zeros Displays trailing zeros.
9	9999	Displays a value with the number of digits specified by the number of 9s. Value has a leading space if positive, a leading minus sign if negative. Blanks are displayed for leading zeroes. A zero (0) is displayed for a value of zero.
B	B9999	Displays blanks for the integer part of a fixed-point number when the integer part is zero, regardless of zeros in the format model.
C	C999	Displays the ISO currency symbol in the specified position.
D	99D99	Displays the decimal character to separate the integral and fractional parts of a number.
EEEE	9.999EEEE	Displays value in scientific notation (format must contain exactly four "E"s).
G	9G999	Displays the group separator in the specified positions in the integral part of a number.

Element	Examples	Description
L	L999	Displays the local currency symbol in the specified position.
MI	9999MI	Displays a trailing minus sign after a negative value. Displays a trailing space after a positive value.
PR	9999PR	Displays a negative value in <angle brackets>. Displays a positive value with a leading and trailing space.
RN rn	RN rn	Displays uppercase Roman numerals. Displays lowercase Roman numerals. Value can be an integer between 1 and 3999.
S	S9999 9999S	Displays a leading minus or plus sign. Displays a trailing minus or plus sign.
TM	TM	Displays the smallest number of decimal characters possible. The default is TM9. Fixed notation is used for output up to 64 characters, scientific notation for more than 64 characters. Cannot precede TM with any other element. TM can only be followed by a single 9 or E
U	U9999	Displays the dual currency symbol in the specified position.

COMP[UTE] [*function* [LAB[EL] *text*] ... OF {*expr* | *column* | *alias*} ...ON {*expr* | *column* | *alias* | REPORT | ROW} ...]

In combination with the BREAK command, calculates and prints summary lines using various standard computations. It also lists all COMPUTE definitions. The following table lists valid functions. All functions except NUMBER apply to non-null values only. COMPUTE functions are always executed in the following sequence AVG, COUNT, MINIMUM, MAXIMUM, NUMBER, SUM, STD, VARIANCE.

Function	Computes	Applies to Datatypes
AVG	Average of non-null values	NUMBER
COU[NT]	Count of non-null values	All types
MIN[IMUM]	Minimum value	NUMBER, CHAR, NCHAR, VARCHAR2 (VARCHAR), NVARCHAR2 (NCHAR VARYING)
MAX[IMUM]	Maximum value	NUMBER, CHAR, NCHAR, VARCHAR2 (VARCHAR), NVARCHAR2 (NCHAR VARYING)
NUM[BER]	Count of rows	All types
SUM	Sum of non-null values	NUMBER
STD	Standard deviation of non-null values	NUMBER
VAR[IANCE]	Variance of non-null values	NUMBER

REP[Footer] [PAGE] [*printspectext* | *variable*] ... | [ON | OFF]

Places and formats a footer at the bottom of a report, or lists the current REPFOOTER definition.

Where *printspec* represents one or more of the following clauses:

BOLD  
CE[NTER]  
COL *n*  
FORMAT *text*  
LE[FT]  
R[IGHT]  
S[KIP] [*n*]  
TAB *n*

REPH[EADER] [PAGE] [*printspec* [*text* | *variable*] ...] | [ON | OFF]

Places and formats a header at the top of a report, or lists the current REPHEADER definition.

Where *printspec* represents one or more of the clauses shown for REPFOOTER.

SPOOL[OL] [*filename*.[*ext*] [CRE[ATE] | REP[LACE] | APP[END]] | OFF | OUT]

Stores query results in a file, or optionally sends the file to a printer. OFF stops spooling. OUT stops spooling and sends the file to your computer's default printer. Enter SPOOL with no clauses to list the current spooling status. If no file extension is given, the default extension, *.lst* or *.lis*, is used.

TTI[TLE] [*printspec* [*text* | *variable*] ...] | [ON | OFF]

Places and formats a specified title at the top of each report page, or lists the current TTITLE definition. The old form of TTITLE is used if only a single word or a string in quotes follows the TTITLE command.

Where *printspec* represents one or more of the following clauses:

BOLD  
CE[NTER]  
COL *n*  
FORMAT *text*  
LE[FT]  
R[IGHT]  
S[KIP] [*n*]  
TAB *n*

## Accessing Databases

**Use the following commands to access and copy data between tables on different databases.**

CONN[ECT] [{*logon* | /} [AS {SYSOPER | SYSDBA | SYSASM}]]

where *logon* requires the following syntax:

*username*[/*password*] [@*connect\_identifier*] [*edition=value*]

Connects a given username to the Oracle Database. If you omit *connect\_identifier*, SQL\*Plus connects you to the default database. If you omit *username* and/or

*password*, SQL\*Plus prompts you for them. CONNECT followed by a slash (/) connects you using a default (OPS\$) logon.

When you run a CONNECT command, the site profile, glogin.sql, and the user profile, login.sql, are processed in that order. CONNECT does not reprompt for username or password if the initial connection does not succeed.

DISC[ONNECT]

Commits pending changes to the database and logs the current user out of Oracle, but does not exit SQL\*Plus. In SQL\*Plus command line, use EXIT or QUIT to log out of Oracle and return control to your computer's operating system.

COPY {FROM *database* | TO *database* | FROM *database* TO *database*} {APPEND | CREATE | INSERT | REPLACE} *destination\_table*[(*column*, *column*, *column*, ...)] USING *query*

where *database* has the following syntax:

*username*[/*password*]@*connect\_identifier*

Copies data from a query to a table in the same or another database. APPEND, CREATE, INSERT or REPLACE specifies how COPY treats the existing copy of the destination table (if it exists). USING *query* identifies the source table and determines which rows and columns COPY copies from it. COPY supports CHAR, DATE, LONG, NUMBER and VARCHAR2 datatypes.

PASSW[ORD] [*username*]

Allows you to change a password without displaying it on an input device.

XQUERY *xquery\_statement*

Allows you to run an XQuery from SQL\*Plus.

## Miscellaneous

ARCHIVE LOG {LIST | STOP} | {START | NEXT | ALL | *integer*}[TO *destination*]

Starts or stops automatic archiving of online redo logs, manually (explicitly) archives specified redo logs, or displays information about redo log files.

DESC[RIBE] [{*schema*.}]*object*[@*connect\_identifier*]

Lists the column definitions for a table, view or synonym, or the specifications for a function or procedure.

RECOVER {*general* | *managed* | BEGIN BACKUP | END BACKUP}

where the *general* clause has the following syntax:

[AUTOMATIC] [FROM *location*]  
{ {*full\_database\_recovery* | *partial\_database\_recovery* | LOGFILE *filename* }  
[ {TEST | ALLOW *integer* CORRUPTION | *parallel\_clause* }  
[TEST | ALLOW *integer* CORRUPTION | *parallel\_clause* ]...]}CONTINUE  
[DEFAULT] | CANCEL}

where the *full\_database\_recovery* clause has the following syntax:

```
[STANDBY] DATABASE [ {UNTIL {CANCEL | TIME date | CHANGE integer}  
| USING BACKUP CONTROLFILE} [UNTIL {CANCEL  
| TIME date | CHANGE integer} | USING BACKUP CONTROLFILE]...]
```

where the *partial\_database\_recovery* clause has the following syntax:

```
{TABLESPACE tablespace [, tablespace]...  
| DATAFILE {filename | filename | filename | filename}...  
| STANDBY {TABLESPACE tablespace [, tablespace]...  
| DATAFILE {filename | filename} [, filename | filename]...}  
UNTIL [CONSISTENT WITH] CONTROLFILE }
```

where the *parallel* clause has the following syntax:

```
{ NOPARALLEL | PARALLEL [ integer ] }
```

where the *managed* clause has the following syntax:

```
MANAGED STANDBY DATABASE recover_clause | cancel_clause | finish_clause
```

where the *recover\_clause* has the following syntax:

```
{ { DISCONNECT [ FROM SESSION ] | { TIMEOUT integer | NOTIMEOUT } }  
| { NODELAY | DEFAULT DELAY | DELAY integer } | NEXT integer  
| { EXPIRE integer | NO EXPIRE } | parallel_clause  
| USING CURRENT LOGFILE | UNTIL CHANGE integer  
| THROUGH { [ THREAD integer ] SEQUENCE integer  
| ALL ARCHIVELOG | { ALL | LAST | NEXT } SWITCHOVER } }  
[ DISCONNECT [ FROM SESSION ] | { TIMEOUT integer | NOTIMEOUT }  
| { NODELAY | DEFAULT DELAY | DELAY integer } | NEXT integer  
| { EXPIRE integer | NO EXPIRE } | parallel_clause  
| USING CURRENT LOGFILE | UNTIL CHANGE integer  
| THROUGH { [ THREAD integer ] SEQUENCE integer  
| ALL ARCHIVELOG | { ALL | LAST | NEXT } SWITCHOVER } ]...
```

where the *cancel\_clause* has the following syntax:

```
CANCEL [IMMEDIATE] [WAIT | NOWAIT]
```

where the *finish\_clause* has the following syntax:

```
[ DISCONNECT [ FROM SESSION ] ] [ parallel_clause ]  
FINISH [ SKIP [ STANDBY LOGFILE ] ] [ WAIT | NOWAIT ]
```

where the *parallel\_clause* has the following syntax:

```
{ NOPARALLEL | PARALLEL [ integer ] }
```

Performs media recovery on one or more tablespaces, one or more datafiles, or the entire database.

SET *system\_variable value*

Sets a system variable to alter the SQL\*Plus environment settings for your current session. For example, to:

- set the display width for data
- customize HTML formatting
- enable or disable printing of column headings

- set the number of lines per page

Enter a system variable followed by a value as shown below:

```

SET APPENDONLY {ON | OFF | text}
SET ARRAYSIZE {15 | n}
SET AUTO[COMMIT] {ON | OFF | IMMEDIATE | n}
SET AUTOPRINT {ON | OFF}
SET AUTORECOVERY {ON | OFF}
SET AUTOTRACE {ON | OFF | TRACE[ONLY]} [EXPLAIN] [STATISTICS]
SET BLOCKTERMINATOR {_ | c | ON | OFF}
SET CMDS[EP] {; | c | ON | OFF}
SET COLSEP {_ | text}
SET CONCAT {_ | c | ON | OFF}
SET COPYCOMMIT {0 | n}
SET COPYTYPECHECK {ON | OFF}
SET DEFINE {& | c | ON | OFF}
SET DESCRIBE [DEPTH {1 | n | ALL}] [LINENUM {ON | OFF}] [INDENT {ON | OFF}]
SET ECHO {ON | OFF}
SET EDITFILE file_name[.ext]
SET EMBEDDED {ON | OFF}
SET ERRORLOGGING {ON | OFF} [TABLE [schema.]tablename] [TRUNCATE] [IDENTIFIER
identifier]
SET ESCAPE [_ | c | ON | OFF]
SET ESCCHAR {@ | ? | % | $ | OFF}
SET FEEDBACK {6 | n | ON | OFF}
SET FLAGGER {OFF | ENTRY | INTERMEDIATE | FULL}
SET FLUSH {ON | OFF}
SET HEADING {ON | OFF}
SET HEADSEP {_ | c | ON | OFF}
SET INSTANCE [instance_path | LOCAL]
SET LINE[SIZE] {80 | n}
SET LOBOFFSET {n | 1}
SET LOGSOURCE [pathname]
SET LONG {80 | n}
SET LONGC[HUNKSIZE] {80 | n}
SET MARKUP HTML [ON | OFF] [HEAD text] [BODY text] [TABLE text]
[ENTMAP {ON | OFF}] [SPOOL {ON | OFF}] [PREFORMAT {ON | OFF}]
SET NEWPAGE {1 | n | NONE}
SET NULL text
SET NUMFORMAT format
SET NUMWIDTH {10 | n}
SET PAGESIZE {14 | n}
SET PAUSE {ON | OFF | text}
SET RECSEP {WRAPPED | EA[CH] | OFF}
SET RECSEPCHAR {_ | c}
SET SERVEROUTPUT {ON | OFF} [SIZE {n | UNLIMITED}] [FORMAT {WRAPPED
| WORD_WRAPPED | TRUNCATED}]
SET SHIFT[INOUT] {VISIBLE | INVISIBLE}
SET SHOW[MODE] {ON | OFF}
SET SQLBLANKLINES {ON | OFF}
SET SQLCASE {MIXED | LOWER | UPPER}
SET SQLCONTINUE {> | text}
SET SQLNUMBER {ON | OFF}
SET SQLPLUSCOMPATIBILITY {x.y.z}

```

SET SQLPRE[FIX] {# | c}  
 SET SQLP[ROMPT] {SQL> | text}  
 SET SQLT[ERMINATOR] {: | c | ON | OFF}  
 SET SUF[FIX] {SQL | text}  
 SET TAB {ON | OFF}  
 SET TERM[OUT] {ON | OFF}  
 SET TI[ME] {ON | OFF}  
 SET TIMI[NG] {ON | OFF}  
 SET TRIM[OUT] {ON | OFF}  
 SET TRIMS[POOL] {ON | OFF}  
 SET UND[ERLINE] {: | c | ON | OFF}  
 SET VER[IFY] {ON | OFF}  
 SET WRA[P] {ON | OFF}  
 SET XQUERY BASEURI {text}  
 SET XQUERY ORDERING {UNORDERED | ORDERED | DEFAULT}  
 SET XQUERY NODE {BYVALUE | BYREFERENCE | DEFAULT}  
 SET XQUERY CONTEXT {text}

SHOW[W] [option]

Shows the value of a SQL\*Plus system variable, or the current SQL\*Plus environment. Enter any system variable set by the SET command in place of *system\_variable*. SHOW SGA requires a DBA privileged login. Use one of the following terms or clauses in place of *option*:

*system\_variable*

ALL

BTI[TLE]

ERR[ORS] [ {FUNCTION | PROCEDURE | PACKAGE | PACKAGE BODY | TRIGGER | VIEW | TYPE | TYPE BODY | DIMENSION | JAVA CLASS}

[*schema.*]*name*]

LNO

PARAMETERS [*parameter\_name*]

PNO

RECYC[LEBIN] [*original\_name*]

REL[EASE]

REPF[OOTER]

REPH[EADER]

SGA

SPOO[L]

SPPARAMETERS [*parameter\_name*]

SQLCODE

TTI[TLE]

USER

XQUERY

---

SQL\*Plus Quick Reference, Release 11.1  
B31190-01

Copyright © 1996, 2007, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.



If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

